GINGER					Project:	Туре:
DUS286 White					Cat. No.:	
DUS286 White LED Surface wall luminaire. indirect up/down sconce. Driver included. FIXTURE: Mounting: surface wall Finish: White ("powder coat") Material: Aluminum Damp Location Listed (for use indoors) CSA/US Listed LAMP/LED SOURCE/COLOR TEMP: -930 7W LED / 3000K / CRI ≥ 90 / 810lm Efficacy (CRI ≥ 90): 115lm/W, Rated life > 50000hrs -927 7W LED / 3000K / CRI ≥ 90 / 760lm Efficacy (CRI ≥ 90): 108lm/W, Rated life > 50000hrs -927 7W LED / 3000K / CRI ≥ 90 / 760lm Efficacy (CRI ≥ 90): 108lm/W, Rated life > 50000hrs -927 7U LED / 3000K / CRI ≥ 90 / 760lm Efficacy (CRI ≥ 90): 108lm/W, Rated life > 50000hrs -927 700 Class 2 120Vac/60Hz, TRIAC/ELV dimmable (leading/trailing edge), Power factor ≥ 0.9 / Flicker (THD) ≤ 20%, Constant current 200mA photometric files, dimming compatibility list and warranty information available online at www.dislightingus.com					Cat. No.:	
available online at <u>www.ubsigntingas.com</u>					Shown above: DUS286-white-7W-930-120V-DIM	
Measurements (Inches)					Light Distribution	
4 1/2" 4 1/2" 4 1/2" 6 1/4" 5 3/4"					100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100° 100°	
ORDERING INFORMATION -SUFFIX						
Model Number	Finish	LED Source	Color Temp.	Driver		
DUS286	-white	-7W	-930 -927	-120V-DIM		
Example of Catalog #: DUS286-white-7W-930-120V-DIM					1	
DLS Light 3135 SR 5 Safety Ha www.dlslig <u>dlsus@dls</u>	80, Suite bor, FL 3 htingus.c	4695 om				*DLS